

**DMC
SONORA
CHAMBERS**

dmc 
SONORA

**SOUNDPROOF
CHAMBERS**

**ASSEMBLY TYPE
SOUNDPROOF
ROOM**



www.dmcrf.com

////////////////////
Ultra-Premium Quality
Best Performance
35+ Years Experience

PART#	TYPE	EFFECTIVE (UNIT: MM)	EXTERNAL DIMENSIONS (UNIT: MM)
DMC-L1-NFLR-101921	Light L-1 No Floor	W900 × L1800 × H2100	W1000 × L1900 × H2150
DMC-L1WFLR-101922	Light L-1 With Floor	W900 × L1800 × H2100	W1000 × L1900 × H2250
DMC-L2NFLR-191921	Light L-2 No Floor	W1800 × L1800 × H2100	W1900 × L1900 × H2150
DMC-L2WFLR-191922	Light L-2 With Floor	W1800 × L1800 × H2100	W1900 × L1900 × H2250
DMC-L3NFLR-192821	Light L-3 No Floor	W1800 × L2700 × H2100	W1900 × L2800 × H2150
DMC-L3WFLR-192822	Light L-3 With Floor	W1800 × L2700 × H2100	W1900 × L2800 × H2250
DMC-N1NFLR-101921	Normal N-1 No Floor	W900 × L1800 × H2100	W1050 × L1950 × H2175
DMC-N1WFLR-101922	Normal N-1 With Floor	W900 × L1800 × H2100	W1050 × L1950 × H2275
DMC-N2NFLR-191921	Normal N-2 No Floor	W1800 × L1800 × H2100	W1950 × L1950 × H2175
DMC-N2WFLR-191922	Normal N-2 With Floor	W1800 × L1800 × H2100	W1950 × L1950 × H2275
DMC-N3NFLR-192821	Normal N-3 No Floor	W1800 × L2700 × H2100	W1950 × L2850 × H2175
DMC-N3WFLR-192822	Normal N-3 With Floor	W1800 × L2700 × H2100	W1950 × L2850 × H2275
DMC-H1NFLR-112022	Heavy H-1 No Floor	W900 × L1800 × H2100	W1100 × L2000 × H2200
DMC-H1WFLR-112023	Heavy H-1 With Floor	W900 × L1800 × H2100	W1100 × L2000 × H2300
DMC-H2NFLR-202022	Heavy H-2 No Floor	W1800 × L1800 × H2100	W2000 × L2000 × H2200
DMC-H2WFLR-202023	Heavy H-2 With Floor	W1800 × L1800 × H2100	W2000 × L2000 × H2300
DMC-H3NFLR-202922	Heavy H-3 No Floor	W1800 × L2700 × H2100	W2000 × L2900 × H2200
DMC-H3WFLR-202923	Heavy H-3 With Floor	W1800 × L2700 × H2100	W2000 × L2900 × H2300

INSULATION LEVEL (TRANSMISSION LOSS) / dB										
		Hz	63	125	250	500	1000	2000	4000	8000
Guaranteed Insulation Value	Light L	(14)	20	30	34	39	41	46	45	
	Normal N	(16)	24	34	38	41	46	51	52	
	Heavy H	(20)	31	38	42	46	51	56	56	
Actual Shielding Amount	Light L	18.6	25.0	34.6	41.6	45.5	46.9	52.2	55.5	
	Normal N	25.0	33.5	38.8	51.2	53.6	59.8	61.6	62.9	
	Heavy H	31.0	46.9	45.7	53.5	60.2	62.6	68.7	76.0	

SPECIFICATION

- Single swing soundproof door
- Floor panel (carpet finish) *Excluding cases without flooring
- Utility pipe diameter 65 + sound insulation cover x 2
- Supply and exhaust silencer
- Sound insulation window reinforced glass double layer
- Completed documents (drawings, specifications, measurement reports, etc.)
- Sealed handle + hinge
- Bulb type light, 100V outlet
- Distribution board + switch
- Sirocco fan

OPTIONS

A.C.
Automatic door
Monitor

Various alarm devices
Fire alarm
Earthquake resistant design

Signal light
BNC
Intercom



Diamond Microwave Chambers Ltd
15 Fitzgerald Rd, Suite 200
Ottawa, ON K2H 9G1
Canada
Ph.+1(613) 915 5533
sales@dmcrf.com